SHENZHEN LINGHUFOX TECHNOLOGY CO., LTD.
Focus on Interactive Whiteboard and Solution

LINGHUFOX

Interactive Electronic Whiteboard





(The picture is just for reference, removable stand is optional)

Application:

Office | Education | Conference | Presentation

Highlights:

High Contrast | Wide View | Customization | Android | Windows

Model: LINGHUFOX-65S (65 Inch)

Key Features:

1. Built-in multi-functions whiteboard software (infinite canvas/shape drawing, etc), support 20 points
2. Dual system, Android 11.0(4G+32G) and Windows system is optional.
3. Fast Wireless Screen Sharing for multi-device such as computer, android, iPhone, Mac(4 device at the same time)
4. Compatible with different popular conference software, such as Zoom/Google Meet/Microsoft Teams.
5. An open ecosystem to install various software, just download from Google Play.
6. Integrate TV, Tradition Whiteboard, Audio, AD display, Projector and Computer into one.
7. Suitable for remote video meetings with your teams in other country.
8. With wall mounting rack .

Our Company Advantages:

1. Put quality and service into the first place, have a strict profession team to control the machine quality, have high temperature aging room, transportation&falling test equipment, etc to ensure high quality.
2. Direct cost control, and can offer favorable margin gap.
3. Flexible and professional OEM&ODM support.
4. LOW MOQ support.
5. 24 hours sweet service support

LINGHUFOX



Product Component Description





Product specification

LINGHUFOX

Display	Screen Size	65 inch
	Screen assembly process	Frame/Zero Bonding Technology
	Backlight Type	DLED
	Display Type	2D
	Pixel pitch	0.372 x 0.372mm
	Effective display area	1428*803MM
	Screen Ratio	16:9
	Physical Resolution	3840x 2160 UHD
	Brightness	300-350cd/m^2
	Contrast Ratio	1200： 1 (Typ.)
	Display color	1.06 billion colors
	Viewing Angle	178°,178°
	Refresh	60Hz
	Response Time	8ms
	Audio output power	8Q15W x2
Touch	Touch Type	IR Touch Screen
	Touch Points	The PC supports 20 touch points
	Touch embedding method	Embedded on the side
	Touch drive mode	HID driver-free
	Touch writing surface material	4mm tempered glass + Anti-glare
	Touch screen sensing method	Fingers or other non-transparent touch-sensitive media
	Touch screen positioning resolution	4096X4096
	Touch system communication port	USB 2.0
	Detection function and calibration	With software automatic detection function
	Responding speed	<8ms
	Touch times	Unlimited times
	Scan speed	100Hz/s
	Cursor speed	125P/S
	Touch accuracy	<=2mm
	Installation and maintenance method	Rear\side disassembly maintenance type
	Touch support operating system	XP/Win7/ Win10/ LINUX/ Android

SPECIFICATION	Product Size		No external installation media	
	Size including rack	1486*921*119.9MM	Hanger hole distance:	400*500MM
	Embedded wall installation size		Installation Principle	Single side extra 20mm
	Package Size	1600*205*1001.5MM	Package method	Kraft carton
	N.W./G.W.	37.7Kg/46.5Kg		
	Installation method	Embedded installation (standard)		
	Front Interface	USB*3， HDMI*1， TOUCH *1， Type-C*1		
	Storgage Environment	Storage temperature: -20°C~60°C; storage humidity: 10%RH~90%RH		
	Working Environment	Working temperature: - 10°C~55°C; Working humidity: 10%RH~90%RH		
	Using lifetime	≧50000 hrs		
POWER	Working Volt.	110~240V/50~60Hz	Power switch/position	yes/ rear
	Power consumption	About 200W	Power type/method	Three-core power supply/fixed
	Standby power consumption	≦0.5W	Power interface specification	Y style
Mainboard configuration scheme	Model	C.T982.81		
	System version	Android 11.0		
	To configure	T982-N0DN, CPU(A55*4) , GPU （Mali G52MP2) , CPU Frequency （2GHz）, NPU （ 1T）, DDR(4G~8G) , eMMC(32G~128G), 2.4G +5G Hot spot		
	Input port	RJ45 IN*1， PC AUDIO IN*1, VGA*1, DP*1, RS232*1, USB2.0*1, HDMI*2, USB Type C, USB3.0*2		
	Output port	RJ45 Out*1， HDMI *1, (Mini)LINE Out*1, OPTICAL Out*1, TOUCH Out*1		
	Audio frequency	MPEG1/2 layer I/II,AC-3(To be customized),AAC-Lc,WMA…		
	Video	MPEG- 1/2/4,AVS2 MP,H.264,H265,VP9		
	Picture	JPG/BMP/PNG		

Accessories: Wall-mount bracket, Remote control, Stylus(writing pen), Antenna, Power cable.

Usage scenarios

Remote Video Meeting



Teaching



This 65 inch interactive whiteboard is well compatible with different video software such as Zoom, Microsoft Teams, Skype, etc, which can satisfy to have a remote video meeting, training, medical diagnosis with teams from other country.

Please Note: The price list is at the end of page. Thank you for checking.

SHENZHEN LINGHUFOX TECHNOLOGY CO., LTD.
Focus on Interactive Whiteboard and Solution

LINGHUFOX

QUALITY ASSURANCE

Workshop Environment


Dust-free Workshop


Assembly Line


Aging Line

Manufacturing Process



Assemble Main Board


Assemble Backplates


Assemble LCD Screens

Process Control


Check Assembly


Check Screen



Check Whole Machine

Quality Inspection



PCB Board Test


High&Low Temperature Aging


Package Transport & Falling Test

Production Capacity


Enough Stock


High Production


High Quality

